


Art-Nr.	Typ	BD	A	L	Stück	Stück
		mm	mm	mm	Sack	Palette
222921	Bipo 30 S oD	30	40	40	200	6.400
222931	Bipo 35 S oD	35	40	40	200	6.400
222941	Bipo 40 S oD	40	45	45	175	5.600
222951	Bipo 45 S oD	45	45	45	175	5.600
222961	Bipo 50 S oD	50	50	50	150	4.800
222971	Bipo 55 S oD	55	50	50	125	4.000
222981	Bipo 60 S oD	60	52	55	100	3.200
222986	Bipo 65 S oD	65	54	55	100	3.200
222987	Bipo 70 S oD	70	55	55	75	2.400
222988	Bipo 75 S oD	75	56	55	75	2.400
222989	Bipo 80 S oD	80	57	55	75	2.400



The Bipo S stable without wire is used for horizontal reinforcement. Due to the large contact area, the Bipo is very stable and highly resilient. The Bipo is manufactured with a flat contact surface as standard and can also be supplied with a trough on request. The Bipos contain a hole through which the user can insert a tying wire.

Material-characteristics:

Labeling according to DBV	DBV-c-L2-F-T-A-D
Concrete compressive strength	ca. 50 N/mm ²
Bulk density	2,1 - 2,3 kg/dm ³
Building material class	A1

Technical changes reserved.